

ASX 812

Auto-loading stretcher

The geometrical line rewards the stability and operations of translation and sitting. The advanced setting of the loading carriage gives this stretcher indisputable safety during loading and unloading maneuvers. The wheels of large diameter are appreciated for their capability to absorb the roughness of the terrain and easy handling.


Technical Specifications

- **Efficiency** during loading and unloading maneuvers thanks to the 10G certified fastener Easyblock
- **Color coded commands** for easy and intuitive use
- **Excellent** handling over all terrain thanks to the large diameter of the wheels
- **Sidebars** with quick release mechanism and integrated security system
- **The Bumper** in Santoprene™ protects all sides exposed to impact
- **Aluminum** alloy frame
- **Easy-handling** thanks to the loading system Piuma Load
- **Adjustable** in three possible heights
- **Equipped** with patient belt system
- **Pivoting wheels** with brake
- **Pneumatic** control system for backrest and Trendelenburg
- **Efficiency** during loading and unloading maneuvers thanks to the 10G certified fastener Easyblock
- **Heat Sealed** waterproof mattress
- **Compliant** with UNI EN 1865-1
- **Ambulance locking system** compliant with UNI EN 1789 (optional)
- **Available** in H and L versions which differ in loading heights

| | |
|--------------------------|--------------------------------|
| Length | 1970 mm |
| Width | 570 mm |
| Height (to the mattress) | 900 mm (812L) / 1000 mm (812H) |
| Loading carriage height | 590 mm (812L) / 690 mm (812H) |
| Sidebars height | 195 mm |
| Sidebars length | 620 mm |
| Wheels | ø200 mm |
| Weight | 45 kg |
| Materials | Aluminum, PE, PVC |
| Loading capacity | 200 kg |



ASX 812



Rev.1 (29/12/2014)

To verify if the information here reported is correct and up to date please contact AMOS
info@amos1.com | www.amos1.com

