

ASX 811

Moving ASX 811 is just a great feeling. Immediately evident to the eye are the handling structures and the command group. ASX 811 anticipates a new style, matching sinuous shapes with the technology of the loading system Piuma Load.

Technical Specifications

- **Efficiency** during loading and unloading of the stretcher thanks to the 10G fixing system easyblock
- **Color coded commands** allow easy and intuitive use
- **Excellent** handling over all terrain thanks to the large diameter of the wheels
- **Sidebars** with quick release mechanism and integrated security system
- **The Bumper** in Santoprene™ protects the sides exposed to impacts
- **Aluminum** alloy frame
- **Loading** and unloading of the stretcher is easier thanks to the loading system Piuma Load
- **Equipped** with belts system for patient
- **Rear wheels** pivoting with brake
- **Pneumatic** control system for backrest and Trendelenburg
- **Heat Sealed** waterproof mattress
- **Compliant** with UNI EN 1865-1
- **Ambulance locking system** compliant with UNI EN 1789 (optional)
- **Available** in H and L versions which differ in loading heights

Length	1970 mm
Width	570 mm
Height (to the mattress)	900 mm (811L) / 1000 mm (811H)
Loading carriage height	590 mm (811L) / 690 mm (811H)
Sidebars height	195 mm
Sidebars length	620 mm
Wheels	ø200 mm
Weight	45 kg
Materials	Aluminum, PE, PVC
Loading capacity	200 kg



ASX 811



Rev.1 (29/12/2014)

To verify if the information here reported is correct and up to date please contact AMOS
info@amos1.com | www.amos1.com

