

# ASX 812

The geometrical line rewards the stability and the operations of translation and sitting. The advanced setting of the loading carriage gives this stretcher an indisputable safety during loading and unloading maneuvers. The wheels of large diameter are appreciated for their capability to absorb the roughness of the terrain and for making the handling of the ASX 812 easier.


## Technical Specifications

- **Efficiency** during loading and unloading of the stretcher thanks to the 10G fixing system easyblock
- **Color coded commands** allow easy and intuitive use
- **Excellent** handling over all terrain thanks to the large diameter of the wheels
- **Sidebars** with quick release mechanism and integrated security system
- **The Bumper** in Santoprene™ protects the sides exposed to impacts
- **Aluminum** alloy frame
- **Loading** and unloading of the stretcher is easier thanks to the loading system Piuma Load
- **Adjustable** in three possible heights
- **Equipped** with belts system for patient
- **Rear wheels** pivoting with brake
- **Pneumatic** control system for backrest and Trendelenburg
- **Heat Sealed** waterproof mattress
- **Compliant** with UNI EN 1865-1
- **Ambulance locking system** compliant with UNI EN 1789 (optional)
- **Available** in H and L versions which differ in loading heights

Length	1970 mm
Width	570 mm
Height (to the mattress)	900 mm (812L) / 1000 mm (812H)
Loading carriage height	590 mm (812L) / 690 mm (812H)
Sidebars height	195 mm
Sidebars length	620 mm
Wheels	ø200 mm
Weight	45 kg
Materials	Aluminum, PE, PVC
Loading capacity	200 kg



## ASX 812



Rev.1 (29/12/2014)

To verify if the information here reported is correct and up to date please contact AMOS  
[info@amos1.com](mailto:info@amos1.com) | [www.amos1.com](http://www.amos1.com)

